

PVC-Coated Conduit



Description

PVC-Coated Galvanized rigid conduit with urethane interior coating protects conductors from mechanical damage and corrosive attack. Electrical continuity is maintained across assembled joints.

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- PROTECH threads – A clear urethane coating over hot galvanized threads
- 12 trade sizes from 1/2" through 6"
- Shipped in 10' lengths with coupling. One "no-charge" coupling is included with each 10' length of conduit
- Plastic thread protector caps are color coded for quick identification of conduit size

Standards

STEEL

- UL 6
- CSA C22.2
- ANSI C80.1



*Both PVC and zinc coatings have been investigated as primary protection against corrosion. Restricted for use with threaded fittings only.

Product Information

Metric Size Designators	Pipe Size Inches	Catalog #	Outside Wall Thickness Inches	Diameter With Coating Inches	Internal Inside Diameter Inches	Length Without Coupling
16	1/2"	RSC15P	0.14	0.92	0.63	9.941'
21	3/4"	RCS20P	0.15	1.13	0.84	9.941'
27	1"	RSC25P	0.17	1.40	1.06	9.925'
35	1-1/4"	RSC32P	0.17	1.74	1.39	9.925'
41	1-1/2"	RSC40P	0.18	1.98	1.62	9.925'
53	2"	RSC50P	0.19	2.46	2.08	9.925'
63	2-1/2"	RSC65P	0.23	2.96	2.49	9.875'
78	3"	RSC80P	0.25	3.58	3.09	9.875'
91	3-1/2"	RSC90P	0.26	4.08	3.57	9.859'
103	4"	RSC100P	0.27	4.58	4.05	9.859'
129	5"	RSC125P	0.29	5.64	5.07	9.826'
155	6"	RSC150P	0.31	6.71	6.09	9.826'