


Knockout Hubs



Description

Procoat PVC-coated watertight knockout hubs are designed to connect rigid conduit to electrical enclosures through knockout openings. ST hubs are supplied without a grounding lug, while STG and STGM models incorporate a grounding lug. ST and STG models are available in trade sizes from 1/2" through 4", while STGM models are available from 1/2" through 6". The hubs feature an exterior PVC coating and an interior urethane coating for corrosion protection.

Features

- 40 mil PVC exterior coating
- 2 mil urethane interior coating
- ST series: Cast zinc construction, without grounding lug
- STG series: Cast zinc construction, with grounding lug
- STGM series: Malleable iron construction, with grounding lug
- ST and STG: 10 trade sizes from 1/2" through 4"
- STGM: 12 trade sizes from 1/2" through 6"

Standards

UL File No.: E509375

ZINC ONLY: ST, STG


- UL 514B

NEC/CEC

- Class I, Division 2
- Class II, Division 1 & 2
- Class III, Division 1 & 2


NOTE: All screw-tight hubs are listed for NEMA and UL type enclosures 2, 3, 3R, 4, 4X, 11, and 12. Grounding and bonding hubs are listed for NEMA Enclosures 2, 3, 3R, 4, 4X, and 12.

ST				
Cat. No.	Trade Size	A	B	C
ST15P	1/2"	1.34	2.00	0.81
ST20P	3/4"	1.47	2.25	0.91
ST25P	1"	1.66	2.50	1.03
ST32P	1-1/4"	1.69	3.25	1.03
ST40P	1-1/2"	1.69	3.50	1.03
ST50P	2"	1.75	4.25	1.09
ST65P	2-1/2"	2.22	4.75	1.28
ST80P	3"	2.31	5.25	1.38
ST90P	3-1/2"	2.38	5.50	1.44
ST100P	4"	3.00	6.25	1.50




ST

STG				
Cat. No.	Trade Size	A	B	C
STG15P	1/2"	1.34	2.00	0.81
STG20P	3/4"	1.47	2.25	0.91
STG25P	1"	1.66	2.50	1.03
STG32P	1-1/4"	1.69	3.25	1.03
STG40P	1-1/2"	1.69	3.50	1.03
STG50P	2"	1.75	4.25	1.09
STG65P	2-1/2"	2.22	4.75	1.28
STG80P	3"	2.31	5.25	1.38
STG90P	3-1/2"	2.38	5.50	1.44
STG100P	4"	2.44	6.25	1.50



STG

STGM				
Cat. No.	Trade Size	A	B	C
STG15PM	1/2"	1.32	1.19	0.59
STG20PM	3/4"	1.44	1.60	0.78
STG25PM	1"	1.78	1.85	0.99
STG32PM	1-1/4"	1.81	2.17	1.31
STG40PM	1-1/2"	1.93	2.72	1.53
STG50PM	2"	2.03	3.18	1.96
STG65PM	2-1/2"	2.46	3.54	2.34
STG80PM	3"	2.74	4.23	2.91
STG90PM	3-1/2"	3.23	4.59	3.37
STG100PM	4"	3.82	5.20	3.82
STG125PM	5"	4.43	6.62	4.79
STG150PM	6"	4.73	7.45	5.76



STGM